

PATENT COOPERATION TREATY

PCT

INTERNATIONAL SEARCH REPORT

(PCT Article 18 and Rules 43 and 44)

Applicant's or agent's file reference PH-938-PCT	FOR FURTHER ACTION see Notification of Transmittal of International Search Report (Form PCT/ISA/220) as well as, where applicable, item 5 below.	
International application No. PCT/JP 00/ 03554	International filing date (day/month/year) 01/06/2000	(Earliest) Priority Date (day/month/year) 01/06/1999
Applicant HITACHI SOFTWARE ENGINEERING CO., LTD. et al.		

This International Search Report has been prepared by this International Searching Authority and is transmitted to the applicant according to Article 18. A copy is being transmitted to the International Bureau.

RECEIVED

FEB 26 2002

This International Search Report consists of a total of 3 sheets.

☒ It is also accompanied by a copy of each prior art document cited in this report.

TECH CENTER 1600/2900

1. Basis of the report

- a. With regard to the **language**, the international search was carried out on the basis of the international application in the language in which it was filed, unless otherwise indicated under this item.

☐ the international search was carried out on the basis of a translation of the international application furnished to this Authority (Rule 23.1(b)).

- b. With regard to any **nucleotide and/or amino acid sequence** disclosed in the international application, the international search was carried out on the basis of the sequence listing :

☐ contained in the international application in written form.

☐ filed together with the international application in computer readable form.

☐ furnished subsequently to this Authority in written form.

☐ furnished subsequently to this Authority in computer readable form.

☐ the statement that the subsequently furnished written sequence listing does not go beyond the disclosure in the international application as filed has been furnished.

☐ the statement that the information recorded in computer readable form is identical to the written sequence listing has been furnished

2. ☐ **Certain claims were found unsearchable** (See Box I).

3. ☐ **Unity of invention is lacking** (see Box II).

4. With regard to the **title**,

☒ the text is approved as submitted by the applicant.

☐ the text has been established by this Authority to read as follows:

5. With regard to the **abstract**,

☒ the text is approved as submitted by the applicant.

☐ the text has been established, according to Rule 38.2(b), by this Authority as it appears in Box III. The applicant may, within one month from the date of mailing of this international search report, submit comments to this Authority.

6. The figure of the **drawings** to be published with the abstract is Figure No.

☒ as suggested by the applicant.

☐ because the applicant failed to suggest a figure.

☐ because this figure better characterizes the invention.

1

☐ None of the figures.

INTERNATIONAL SEARCH REPORT

International Application No

PCT/JP 00/03554

A. CLASSIFICATION OF SUBJECT MATTER

IPC 7 C12Q1/68 B01J19/00 G01N33/50

According to International Patent Classification (IPC) or to both national classification and IPC

B. FIELDS SEARCHED

Minimum documentation searched (classification system followed by classification symbols)

IPC 7 B01J G01N C12Q

Documentation searched other than minimum documentation to the extent that such documents are included in the fields searched

Electronic data base consulted during the international search (name of data base and, where practical, search terms used)

EPO-Internal, MEDLINE, BIOSIS

C. DOCUMENTS CONSIDERED TO BE RELEVANT

Category °	Citation of document, with indication, where appropriate, of the relevant passages	Relevant to claim No.
X	US 5 812 272 A (KING DAVID A ET AL) 22 September 1998 (1998-09-22) column 11, line 32 - line 57 ----	1-8
A	US 5 677 197 A (CONRADSON SCOTT A ET AL) 14 October 1997 (1997-10-14) column 3, line 20 -column 6, line 10; claims 1-4; figures 1,2 ----	1-8
A	US 5 840 485 A (KOCIS PETER ET AL) 24 November 1998 (1998-11-24) column 3, line 25 - line 45 claims 1-47; example 13 -----	1,2,4,7



Further documents are listed in the continuation of box C.



Patent family members are listed in annex.

° Special categories of cited documents:

- *A* document defining the general state of the art which is not considered to be of particular relevance
- *E* earlier document but published on or after the international filing date
- *L* document which may throw doubts on priority claim(s) or which is cited to establish the publication date of another citation or other special reason (as specified)
- *O* document referring to an oral disclosure, use, exhibition or other means
- *P* document published prior to the international filing date but later than the priority date claimed

T later document published after the international filing date or priority date and not in conflict with the application but cited to understand the principle or theory underlying the invention

X document of particular relevance; the claimed invention cannot be considered novel or cannot be considered to involve an inventive step when the document is taken alone

Y document of particular relevance; the claimed invention cannot be considered to involve an inventive step when the document is combined with one or more other such documents, such combination being obvious to a person skilled in the art.

* & * document member of the same patent family

Date of the actual completion of the international search

13 November 2001

Date of mailing of the international search report

20/11/2001

Name and mailing address of the ISA

European Patent Office, P.B. 5818 Patentlaan 2
NL - 2280 HV Rijswijk
Tel. (+31-70) 340-2040, Tx. 31 651 epo nl,
Fax: (+31-70) 340-3016

Authorized officer

van Klompenburg, W

INTERNATIONAL SEARCH REPORT

Information on patent family members

International Application No

PCT/JP 00/03554

Patent document cited in search report		Publication date	Patent family member(s)	Publication date
US 5812272	A	22-09-1998	DE 19731479 A1 JP 11044647 A	06-08-1998 16-02-1999
US 5677197	A	14-10-1997	NONE	
US 5840485	A	24-11-1998	AU 686186 B2 AU 7048694 A CA 2163637 A1 EP 0705279 A1 JP 9501490 T NZ 267843 A WO 9428028 A1 US 6090912 A	05-02-1998 20-12-1994 08-12-1994 10-04-1996 10-02-1997 24-10-1997 08-12-1994 18-07-2000

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
7 December 2000 (07.12.2000)

PCT

(10) International Publication Number
WO 00/73504 A2

(51) International Patent Classification⁷: C12Q 1/68

(21) International Application Number: PCT/JP00/03554

(22) International Filing Date: 1 June 2000 (01.06.2000)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
11/153540

1 June 1999 (01.06.1999) JP

(71) Applicant (for all designated States except US): HITACHI SOFTWARE ENGINEERING CO., LTD. [JP/JP]; 6-81, Onoe-cho, Naka-ku, Yokohama-shi, Kanagawa 231-8475 (JP).

(72) Inventors; and

(75) Inventors/Applicants (for US only): TAMURA, Takuro [JP/JP]; Hitachi Software Engineering Co., Ltd., 6-81, Onoe-cho, Naka-ku, Yokohama-shi, Kanagawa 231-8475 (JP). YAMAMOTO, Kenji [JP/JP]; Hitachi Software

Engineering Co., Ltd., 6-81, Onoe-cho, Naka-ku, Yokohama-shi, Kanagawa 231-8475 (JP). WATANABE, Toshimasa [JP/JP]; Hitachi Software Engineering Co., Ltd., 6-81, Onoe-cho, Naka-ku, Yokohama-shi, Kanagawa 231-8475 (JP). YOSHII, Jyunji [JP/JP]; Hitachi Software Engineering Co., Ltd., 6-81, Onoe-cho, Naka-ku, Yokohama-shi, Kanagawa 231-8475 (JP).

(74) Agents: HIRAKI, Yusuke et al.; Toranomon No. 5 Mori Building, 3rd floor, 17-1, Toranomon 1-chome, Minato-ku, Tokyo 105-0001 (JP).

(81) Designated State (national): US.


(84) Designated States (regional): European patent (DE, FR, GB).

Published:

— Without international search report and to be republished upon receipt of that report.

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: MICROARRAY CHIP AND METHOD FOR INDEXING THE SAME



(57) Abstract: A method for specifying element information that should be used for a microarray chip in use. Some of element spots (15) arranged on a microarray chip (10) are used as an index (17). By doing so, the microarray chip can be specified and management of the element information and use of the experimental information can be done automatically.

WO 00/73504 A2

Description

MICROARRAY CHIP AND METHOD FOR INDEXING THE SAME

TECHNICAL FIELD

The present invention relates to a microarray chip having a plurality of biopolymer spots arranged thereon such as DNAs or the like that specifically hybridize with particular DNAs or proteins, and to a method for indexing the microarray chip for identification.

BACKGROUND ART

In the field of molecular biology, microarray chips, as represented by a biochip on which biopolymers such as DNAs or proteins are high-densely immobilized, have lately and rapidly become of interest. For an experiment using the microarray chip, numbers of supports (chips) with diverse types of elements (probes) immobilized thereon are produced. The elements on each chip are subjected to reaction with a sample (target) of a test subject. The difference of the reaction between the elements and the sample on one chip may be detected by a single experiment. The difference of the reaction between the same element collections on a plurality of chips may be detected by repeating experiments under different conditions.

In an experiment using a microarray chip, it is necessary to manage the information of diverse types of elements immobilized on the chip. The following methods are practically used for preparing a microarray chip: a method in which elements prepared in wells are immobilized on a support

such as a glass slide by using a spotter (arrayer); and a method in which elements are synthesized on a support according to a semiconductor producing technique. In both methods, element information (i.e., which element is to be immobilized on which location on the chip) is prepared as data for preparing the microarray chip.

In an experiment using a microarray chip, the results of the experiment are obtained by detecting color development of part of the element collection immobilized on the chip. In detecting the color development, "the color intensities of the elements" are recorded based on the element information obtained for preparing the microarray chip. Then, the difference of color development between the elements and the difference of color development between the element collections on the chips are analyzed.

Since the shapes of the microarray chips are all identical, each individual microarray chip cannot be identified by its appearance, nor can the types of the DNAs immobilized on the chip be identified. As shown in Figure 7, a method is suggested in which letters, numbers or symbols are printed or barcodes are provided as an index outside a element region 101 on a microarray chip 100 so as to specify the element information to be used for the microarray chip 100.

In specifying the element information to be used for each microarray chip by the method of printing letters, numbers, symbols or barcodes outside the element region of the chip, a mechanism for printing (or sticking) letters, numbers, symbols or barcodes on a chip is required. In addition, in using the microarray chip, mechanisms (or an interface that allows input

by an operator) are also required for reading the letter, barcode or the like printed on the chip and for informing the same to an information processing system. As a result, cost of devices such as a letter or barcode reader, input error in case of manual input and the like have been the problems.

Regarding the above-described problems of conventional technique, the present invention aims at providing a microarray chip for which element information to be used can be specified without using letters, barcodes of the like. The present invention also aims at providing a method for indexing a microarray chip for specifying element information to be used for the microarray chip without requiring a special-purpose device for reading the element information such as a letter or barcode reader. The present invention further aims at providing a method for indexing a microarray chip, which enables automatic management of information of the elements on the microarray chip and use of experiment information.

According to the present invention, the above-described aims are accomplished by using some of the spots (element spots) arranged on the microchip array as an index (a microarray index) for managing the element information. According to the present invention, elements themselves are used as an index so that the index can be obtained together with the element information upon reading the microarray chip. Thus, there is no need of preparing a special device for reading the index.

Accordingly, a microarray chip of the invention is characterized by comprising a plurality of spots arranged in a predetermined positional relationship, wherein some of the

plurality of spots provide index information for specifying the microarray chip.

The microarray chip of the invention is also characterized by comprising a plurality of element spots arranged in a predetermined positional relationship, wherein spots which provide index information for specifying the microarray chip are positioned along with the element spots.

The spots constructing the microarray index are preferably added with visible colorant beforehand to confirm the index before the experiment, to align the element region and the index region, and to confirm the chip reading direction.

When the microarray chip is prepared by immobilizing elements prepared in wells on a support such as a glass slide by using a spotter (arrayer), elements already bound with a luminescent substance or elements as index spots which allow accumulation of a luminescent substance on the element spots upon the microarray chip experiment are immobilized with the spotter. When the microarray chip is prepared by synthesizing elements on a support according to a semiconductor producing technique, elements which allow accumulation of a luminescent substance on the element spots upon the microarray chip experiment are synthesized on the support.

As described above, the spots used for constructing the index information include spots containing and spots not containing detective colorant, which the index information is based on the presence and absence of the detective colorant. The detective colorant which is used as a fluorescent label for hybridization reaction may be contained in the index spots prior to hybridization reaction, or may be contained in the

target and be provided to the spots as a result of the hybridization reaction. The elements to be immobilized as a microarray index may be labeled with a detective colorant beforehand so as to allow the use of the microarray chip index before the experiment of reacting with the target.

In reading the microarray chip image with a microarray chip reader, the index information on the microarray chip are read simultaneously with the element information. By providing a microarray index at a predetermined position, the microarray index may be obtained from the readout image of the microarray chip after the reaction.

A method for indexing the microarray chip according to the present invention is a method for indexing a microarray chip comprising a plurality of spots arranged in a predetermined positional relationship, wherein some of the plurality of spots are used for maintaining index information.

A method for indexing the microarray chip according to the present invention is further a method for indexing a microarray chip comprising a plurality of spots arranged in a predetermined positional relationship, wherein some of the plurality of spots are used as index spots for maintaining index information, and the index information is reproduced by detecting the presence or absence of a detective colorant on the index spots.

In an experiment using a microarray chip where elements which allow accumulation of a luminescent substance on the element spots are immobilized or synthesized on a support, colored ('on') spots for constructing the microarray index are obtained by immobilizing or synthesizing, on a support, a

substance that reacts with a substance labeled with a colorant which is present in a sample during the course of the experiment, or a substance that reacts with a substance labeled with a colorant added to the sample. Thus, spot detection is ensured.

Moreover, spot detection error can be avoided by providing parity spots. For example, information detected at the index spots is realigned into a two-dimensional matrix upon reproducing the index information, and part of the spot information of the realigned two-dimensional matrix is used as parity information. If necessary, microarray index may be duplicated by providing them at two positions in the element region, thereby avoiding spot detection error.

Database which uses the microarray as an index may be constructed for storing microarray chip information (preparation date, on-chip-spot location information, conditions of the experiment, etc.) and on-chip-element information (element index, experiment measurement information, etc.). The database also stores element information (index for referring to a public database, gene name, definition of the functions, DNA sequence, etc.) and links with information of the element on chip via the element index. By linking the actual microarray chip and the information in the database via the microarray index obtained from the microarray chip readout image, measurement information can automatically be input into the database.

Specifically, a database is constructed for storing a element information record, a microarray chip master record and an on-chip-element information record. Information of a

element is recorded on the element information record where a element index is used as a master index. Information of the microarray chip is recorded on the microarray chip master record where the microarray index is used as a master record. The microarray index, a location of a spot on the microarray chip, element index of the element spotted on that location, and the information of measurement of the spot are recorded on the on-chip-element information record. The microarray chip is linked with the microarray chip master record via the microarray index maintained by the index spots, as well as to the on-chip-element information record. The on-chip-element information record is linked with the element information record via the element index.

BRIEF DESCRIPTION OF THE DRAWINGS

Figures 1A and 1B are schematic views showing an exemplary microarray chip of the present invention;

Figure 2 is a view showing an exemplary microarray provided with a microarray index;

Figures 3A to 3C are views for illustrating an exemplary relationship between the index spots in the microarray and index information;

Figures 4A to 4D are views for illustrating other exemplary arrangements of the index spots;

Figures 5A to 5C are views for illustrating other exemplary arrangements of the index spots;

Figure 6 is a diagram for illustrating links between microarray chips and information in database via microarray indices; and

Figure 7 is a view for illustrating a conventional microarray index.

BEST MODE FOR CARRYING OUT THE INVENTION

Hereinafter, embodiments for carrying out the present invention will be described with reference to the drawings.

Figures 1A and 1B are schematic views showing an exemplary microarray chip provided with a microarray index of the invention. As shown in Figure 1A, the microarray chip 10 includes a support (chip) 11 such as a glass slide, or a nylon or nitrocellulose membrane, and a element region 12 provided on the support 11. As shown in Figure 1B, the element region 12 is provided with a microarray 16 in which element spots 15 are high-densely arranged in a two-dimensional array formation by depositing biopolymers such as DNAs or proteins prepared in wells (not shown) on the chip 11 using a spotter (arrayer). Some of the element spots 15 arranged in a two-dimensional array formation to construct the microarray 16 are used as a microarray index 17 as will be described below.

Figure 2 is a view showing an example of the microarray 16 provided with a microarray index 17 which has an information content of 128 bits according to the present invention. According to this example, four spots are provided per millimeter. One vertical column of the microarray 16 (which consists of 81 x 81 spots arranged within a 20 mm square element region 12) is used as the microarray index 17. Thus, 81 spots are available as an index, and each spot may or may not be immobilized with a color developing colorant or with a element which enables to accumulate a color developing colorant

upon the microarray chip experiment, thereby obtaining 81-bit ON/OFF information. If two color developing colorants (e.g., Cy3 and Cy5) are used for the color development of the elements, each color component can make use of 81 spots since the developed color components from the two co-existing luminescent colorants may separately be detected with a microarray chip reader. According to this method, information of $81 \times 2 = 162$ bits may be used as an index.

Figures 3A to 3C are views for illustrating an exemplary relationship between the 81 index spots in the microarray 16 shown in Figure 2 and the index information. According to this example, 81 index spots are rearranged into a 9×9 grid 23 as shown in Figure 3A in order to efficiently provide parity for detecting any error of any spot at a particular position. Spots in a vertical column at the very right and a horizontal row at the very bottom of the rearranged 9×9 grid are used as parity spots 27. The rest of the spots 26 are used for index information and thus the index spots 26 are made up of $8 \times 8 = 64$ spots.

Each spot is provided with two pieces of information with the two types of luminescent colorants A and B. The colorant A gives information 24 of $8 \times 8 = 64$ spots (64 bits) as shown in Figure 3B, and the colorant B gives information 25 of $8 \times 8 = 64$ spots (64 bits) as shown in Figure 3C. The parity is set for each piece of information with each colorant and for each column and row of the index spots 26 such that, for example, it is ON if the number of ON spots is an odd number and OFF if an even number. The spot at the right bottom corner is ON if the number of ON spots in the whole index area

is an odd number and OFF if an even number. According to this method, highly reliable 64 bit index can be obtained, and 128 bit index can be obtained by using two luminescent colorants.

Figures 4A to 4D are views for illustrating other exemplary arrangements of the index spots. Referring to Figure 4A, index spots are dispersively located in the microarray 16. In this example, the index spots are divided into 9 spot groups 41a to 41i and dispersively located at known locations in the microarray 16. The spot groups 41a to 41i in the microarray 16 do not need to be located in a systematic pattern as long as their locations are known. These spot groups are used as index information by rearranging them as shown in Figures 3A. Referring to Figure 4B, an index spot column 42 is provided outside the microarray 16 made of the element spots. The index spot column 42 is not limited to a single column and multiple may be formed. The index spot columns may also be provided on both sides of the microarray 16.

Figure 4C shows an example where two index spot columns are provided. An index spot column 43a provided on left of the microarray 16 and an index spot column 43b provided at the middle of the microarray 16 may form one index together, or the two spot columns 43a and 43b may carry the same information so that one can be used for verification. Figure 4D shows an example where two index spot columns 44a and 44b having the same functions as those described with reference to Figure 4C are provided at both sides of the microarray 16.

Figures 5A to 5C are views for further illustrating other exemplary arrangements of the index spots. In examples shown in Figures 5A and 5B, element spots are positioned to

form concentric circles on a circular microarray chip. As a whole, the microarray forms a circle. Each element spot on the microarray can be specified with a record 53 which is determined by a distance from the center (radius) of the microarray and a rotation angle 54 determined based on a marker 52 which determines the starting position of the rotation. Some of the spots in the microarray can be used as index spots. Figure 5A shows an example where sequential spots 55a at the outermost record (record 0) of the microarray 51a and between the rotation angles of 0° and 45° are used as the index spots. Figure 5B shows an example where sequential spots 55b and 55c at the outermost record 0 and between the rotation angles of 0° and 45° and between 90° and 135° , respectively, are used as the index spots.

According to the example shown in Figure 5C, each element spot are arranged at equal intervals in a vortex pattern starting from the marker 57 which determines the starting position of the vortex. As a whole, the microarray 51c forms a circle. Each element spot on the microarray 51c can be specified by a distance from the marker 57. Some of the spots on the microarray can be used as index spots. Figure 5C shows an example where a plurality of element spots 58 following immediately after the marker 57 for determining the starting position of the vortex are used as index spots.

Figure 6 is a diagram for illustrating links between microarray chips and information in database via a microarray indices. In a microarray chip information database 60, element information that can be used for preparing microarray chips is stored as element information records 63 where element indices

(i_elmid) are used as master indices. The element information record 63 stores, according to the type of the element, an index (acc_num) for referring to a public database containing the information of the elements, designations of the gene/protein, biological functions and gene/amino acid sequence as element information.

In preparing the microarray chip 10, a microarray index (with a unique value of, for example, 128 bits) is issued, and microarray chip master records 61 which use the microarray indices (r_aryid) as master indices are added to the microarray chip information database 60. The microarray chip master records 61 store information of the microarray chip to be prepared (date of preparation, comments, etc.) and is provided with a field for storing, for example, conditions of a microarray chip experiment. Furthermore, on-chip-element information records 62 are generated for the same number as that of the elements to be immobilized on the microarray chip and are linked via the same microarray index (65). Each of the on-chip-element information records 62, stores a location of one element on the microarray chip, and stores a element index to be linked (66) to the element information record. A field for storing later-obtained information of a microarray chip experiment and the like is also provided for each element on the microarray chip.

The results of the microarray chip experiment obtained by a microarray chip reader, together with the microarray index prepared on the microarray chip, can automatically be stored in the microarray chip master record 61 specified by the link via the microarray index (64) and in the on-chip-element

information record 62 linked with the microarray chip master record.

When the results of the experiment is to be referred in the database 60, detailed information of the element can be obtained from the element information record 63 which links with the on-chip-element information record 65. Since the element information record 63 is independent from the microarray index, it may be shared with a plurality of microarray chip master record 61. Further information can be obtained from the public database 70 by linking (67) to the public database via the index for the public database reference stored in the element information record 63.

INDUSTRIAL APPLICABILITY

According to the present invention, information used for microarray chip application can be automatically managed. Without requiring the user of the microarray chip for a special instrument, a microarray index allows link between information of the microarray experiment and information prepared upon making the microarray chip.

CLAIMS

1. A microarray chip comprising a plurality of spots arranged in a predetermined positional relationship, wherein some of the plurality of spots provide index information for specifying the microarray chip.
2. A microarray chip comprising a plurality of element spots arranged in a predetermined positional relationship, wherein spots which provide index information for specifying the microarray chip are positioned along with the element spots.
3. A microarray chip according to claim 1 or 2, wherein the spots which provide index information include spots containing a detective colorant and spots free of the detective colorant so as to give index information by the presence and absence of the detective colorant.
4. A method for indexing a microarray chip comprising a plurality of spots arranged in a predetermined positional relationship, wherein some of the plurality of spots are used for maintaining index information.
5. A method for indexing a microarray chip comprising a plurality of spots arranged in a predetermined positional relationship, wherein some of the plurality of spots are used as index spots for maintaining index information, and the index information is reproduced by detecting the presence or absence of a detective colorant on the index spots.

6. A method for indexing a microarray chip according to claim 5, wherein information detected at the index spots is realigned into a two-dimensional matrix upon reproducing the index information, and part of the spot information of the realigned two-dimensional matrix is used as parity information.

7. A method for indexing a microarray chip according to any one of claims 4, 5 and 6, comprising the steps of:

constructing a database for storing a element information record, a microarray chip master record and an on-chip-element information record;

recording information of a element on the element information record where a element index is used as a master index;

recording information of the microarray chip on the microarray chip master record where the microarray index is used as a master record;

recording, on the on-chip-element information record, the microarray index, a location of a spot on the microarray chip, element index of the element spotted on that location, and the information of measurement of the spot;

linking the microarray chip with the microarray chip master record via the microarray index maintained by the index spots, as well as to the on-chip-element information record; and

linking the on-chip-element information record with the element information record via the element index.




Fig. 1A




Fig. 1B

Fig. 2





Fig.3A




Fig. 3B




Fig. 3C




Fig. 4A




Fig. 4B




Fig. 4C




Fig. 4D




Fig. 5A




Fig. 5B




Fig. 5C

Fig. 6




Fig. 7

